

## SYLVAROS™ DRS 731 Disproportionated Rosin Soap

### PRODUCT DATA SHEET

SYLVAROS DRS 731 Disproportionated Rosin Soap is based on disproportionated rosin neutralized with sodium hydroxide solution. It can be used as emulsifier in the polymerization process of styrene-butadiene rubber, nitrile rubber, polychloroprene and acrylonitrile-butadiene-styrene plastics. SYLVAROS DRS 731 Disproportionated Rosin Soap is also suitable for the manufacture of pigments and it can be used in the adhesive industry for enhancing properties of adhesives on basis of casein or polymer emulsions.

#### FEATURES:

- Paste at room temperature
- Suitable for aqueous systems

#### POTENTIAL APPLICATIONS:

- Polymerization of synthetic rubber and plastics
- Pigments
- Adhesives

### SALES SPECIFICATIONS

Property	Test Method*	Specification	Typical Value
Acid Number (mg KOH/g)	AQCM 001	10 - 12	11
Colour, US Rosin Standards	AQCM 062	WG or better	X
Solids (%)	AQCM 008	69 - 71	70
Unsaponifiables (%)	AQCM 011	Max 10	8
Abietic Acid by UV (%)	AQCM 212	Not detectable	0
Dehydroabietic Acid by UV (%)	AQCM 212	Min 34	39
Chloride (%)	AQCM 229	Max 0.1	0
Iron (mg/kg)	AQCM 018	Max 10	4
Acid Number of Resin Component (mg KOH/g)	AQCM 228	150 - 170	160

\*KRATON test methods are available upon request

### TYPICAL PROPERTIES

Property	Test Method*	Typical Value
pH Value, 10% solution in water	AQCM 035	9

\*KRATON test methods are available upon request

#### Contact us:

Almere (NL): +31 (0)36 54 62 800  
 Savannah (US): + 1 (912) 238-6439  
 Shanghai (CN): + 86 21 6434 8898  
[www.kraton.com](http://www.kraton.com)

<p><b>SOLUBILITY</b></p>	<p>SYLVAROS™ DRS 731 Disproportionated Rosin Soap is <u>soluble</u> in most organic solvents.</p>
<p><b>PACKAGING</b></p>	<p>SYLVAROS DRS 731 Disproportionated Rosin Soap is delivered in heated tank trucks, ISO containers or rail cars, or in steel drums (as available).</p>
<p><b>STORAGE RECOMMENDATION</b></p>	<p>SYLVAROS DRS 731 Disproportionated Rosin Soap is solvent-free and may therefore freeze if stored or transported at &lt; 0 °C. Freezing does not affect the use of the product as chemical raw material but the product must be fully homogenized after defrosting. Prior to usage product should be heated to 60 °C to facilitate handling and the storage tank should also be equipped for homogenizing the product as it may separate during a longer period of storage. The content of IBC's and drums should also be homogenized prior to usage, unless full quantity of the container is used at once.</p> <p>When drummed and stored at ambient temperatures SYLVAROS DRS 731 Disproportionated Rosin Soap should have a shelf life of at least 12 months from the date of production.</p>

**Disclaimer**

We cannot anticipate all circumstances, conditions or applications in which this information, our products, or the products of other suppliers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or for the safety or suitability of our products, either alone or in combination with other products. The user of our products bears the responsibility of determining their suitability for a particular application or formulation, or determining that the products or their use do not infringe any intellectual property. Unless otherwise stated in writing, WE MAKE NO WARRANTY REGARDING THE INFORMATION PROVIDED HEREIN OR OUR PRODUCT, EITHER EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY. The buyer assumes all responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products.

KRATON, the KRATON logo, and SYLVAROS are trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2016 Kraton Corporation

**Contact us:**

Almere (NL): +31 (0)36 54 62 800  
 Savannah (US): + 1 (912) 238-6439  
 Shanghai (CN): + 86 21 6434 8898  
[www.kraton.com](http://www.kraton.com)