

SYLVATAL™ D30LR Distilled Tall Oil

PRODUCT DATA SHEET

SYLVATAL D30LR Distilled Tall Oil is a source of tall oil fatty acids having a high tall oil rosins content. The utility of distilled tall oil fatty acid can be found in the long carbon chain (C18), acid function of the carboxyl group (-COOH), or unsaturation of the double bonds. Plus, the rosin acids content adds "cling" and binding properties to such products as: asphalt anti-stripping agents, metalworking fluids, and rubber compounds. SYLVATAL D30LR derivatives are typically inexpensive soaps, amines, amides, and esters. The high rosin content in SYLVATAL D30LR will produce hard, water-resistant alkyd resins.

FEATURES

- Low viscosity, liquid long fatty acid chain
- Monocarboxylic acid functionality
- Low saturated fatty acid content
- High rosin acid content

POTENTIAL APPLICATIONS

- Metalworking fluids
- Concrete form release agents
- Asphalt anti-stripping agents
- Oilfield chemicals
- Alkyd resins
- Varnishes
- Soaps and cleaners

SALES SPECIFICATIONS

Property	Test Method*	Specification	Typical Value
Acid Number(mgKOH/g)	AQCM 001	184 - 192	188
Color, Gardner	AQCM 002	7 Maximum	5
Free Rosin Acids %	AQCM 010	28 - 32	30

*Kraton test methods are available upon request

TYPICAL VALUES

Property	Test Method*	Typical Value
Unsaponifiables %	AQCM 011	4
Titer °C	AQCM 081	2

*Kraton test methods are available upon request

Contact us:

Almere (NL): +31 (0)36 54 62 800
 Savannah (US): + 1 (912) 238-6439
 Shanghai (CN): + 86 21 6434 8898
www.kraton.com

SOLUBILITY	SYLVATAL™ D30LR distilled tall oil is <u>soluble</u> in alcohols, aromatics, esters and ketones and <u>insoluble</u> in water.
COMPATIBILITY	SYLVATAL D30LR distilled tall oil is compatible with other liquid fatty acid and vegetable oils.
PACKAGING	SYLVATAL D30LR distilled tall oil is delivered as liquid in 420 lb net steel drums or as bulk in totes, tank trucks, or tank cars (as available).
STORAGE RECOMMENDATION	<p>When drummed SYLVATAL D30LR Distilled Tall Oil should be stored unopened, dry and below 25 °C (77 °F), and away from direct sunlight. In bulk the product should be stored at 30 – 40 °C (86 – 104 °F), and under nitrogen or other inert gas to avoid discoloration through oxidation.</p> <p>This product has a tendency to crystallize after holding for extended periods of time at ambient temperatures of 25 °C (77 °F) or lower. If precipitation occurs, it does not affect the use of the product as a chemical raw material. Slight heating to about 40 °C (104 °F) dissolves the precipitated material.</p> <p>Under correct conditions SYLVATAL D30LR Distilled Tall Oil should have a shelf life of at least 12 months from the date of production.</p>

Disclaimer

We cannot anticipate all circumstances, conditions or applications in which this information, our products, or the products of other suppliers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or for the safety or suitability of our products, either alone or in combination with other products. The user of our products bears the responsibility of determining their suitability for a particular application or formulation, or determining that the products or their use do not infringe any intellectual property. Unless otherwise stated in writing, WE MAKE NO WARRANTY REGARDING THE INFORMATION PROVIDED HEREIN OR OUR PRODUCT, EITHER EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY. The buyer assumes all responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products.

KRATON, the KRATON logo, and SYLVATAL are trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2016 Kraton Corporation

Contact us:

Almere (NL): +31 (0)36 54 62 800
 Savannah (US): + 1 (912) 238-6439
 Shanghai (CN): + 86 21 6434 8898
www.kraton.com